

CONSTRUCTION AND FEATURES

- Shown: 3078-NA Containment Tank with 1500 lb (200 gal) capacity. Space saving, 30.25 in. l x 30.25 in. w x 85 in. h
- Stainless steel tank bottom and legs. 6 in. (152 mm) high stainless steel legs and floor clearance
- At-a-glance alerts: Power On (green), Tank Full (red), Call for Pickup 75% Full (yellow)
- UL, UL Sanitation Listed (U.S. and Canada)
- Push the button and you are emptying the fryer. What could be easier?
- If the system cannot be directly plumbed, tanks are equipped with a Caddy System hook up. Frontline International's Caddy System is a great method for transporting cooking oil to the containment tank while still reducing mess and the potential for burns. Caddies roll on wheels and are easy to push.
- Heavy-gauge stainless steel exterior. Tanks can be positioned anywhere indoors— nothing to hide here, this is modern and good-looking, made-in-the-USA equipment that exceed all standards.
- Easy to access and service components
- One-year warranty on all parts and components
- Worldwide delivery and installation available
- Insulated exterior tank enclosure available

BENEFITS

- Minimal or no handling of hot waste shortening
- Insurance and Workers' Comp savings
- Less employee downtime
- Labor savings and greater employee safety
- Cleaner grounds and image
- Waste oil of higher value to collection companies
- Avoid pollution fines

Installation and Operating Specifications

Model	3078-NA Containment Tank
Power Requirements	110 V 15 A - 250 V 3.5 A, 50/60 Hz
Installation Space Requirements	30.25 in. l x 30.25 in. w x 85 in. h (762 mm x 762 mm x 2159 mm)
Shortening Capacity	1500 Lb/200 Gal (680 kg/757 l)
Shipping Weight	400 lb (181 kg)
Documentation	Installation guide, Operating guide
Warranty	One-year parts and labor



WASTE COOKING OIL CONTAINMENT TANK – 3078NA



ARI Energy Corp, LLC

